


Stahl

TECHNISCHE DATEN

Betriebstemperatur :	-20°C bis max. +150°C, druckabhängig
Betriebsdruck :	max. PN 16 bar
Material :	Stahl galvanisch verzinkt, nahtlos
Anschlußgewinde :	nach DIN ISO 228/1



Art. Nr.	G"	DN	L mm	L1 mm	ød mm	PN(bar)
98708712-55-65	3/4"	20	80	17	20	16
98708712-55-110	3/4"	20	110	17	20	16
98708712-55-130	3/4"	20	130	17	20	16
98708712-55-190	3/4"	20	165	17	20	16
98708712-66-105	1"	25	105	18	25	16
98708712-66-110	1"	25	110	18	25	16
98708712-66-130	1"	25	130	18	25	16
98708712-66-190	1"	25	190	18	25	16
98708712-77-130	1 1/4"	32	150	20	34	16
98708712-77-150	1 1/4"	32	150	20	34	16
98708712-77-260	1 1/4"	32	260	20	34	16
98708712-88-150	1 1/2"	40	150	22	39	16
98708712-88-260	1 1/2"	40	260	22	39	16
98708712-99-150	2"	50	150	25	50	16
98708712-99-200	2"	50	200	25	50	16
98708712-99-300	2"	50	300	25	50	16